Certificate No: LR26436068TA
Issue Date: 30/06/2026
Expiry Date: 29/06/2031

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Sub-Drill Supply Ltd**
Address	Endeavour Drive, Arnhall Business Park, Westhill, AB32 6UF, United Kingdom
Type	Gasket
Description	End Connection (Production, Wellhead & BOP) Gasket Sub-X™ VX Type 18 ¾" Gasket Type: PN: SUBX18V3 Sub-X™ VX Type 16 ¾" Gasket Type: PN: SUBX16V3
Trade Name	Sub-X™
Application	Offshore
Specified Standard	ISO 10423 (API 6A)(2009) – Petroleum and Natural Gas Industries – Drilling and Production Equipment – Wellhead and Christmas Tree Equipment API 6A (2018) - Specification for Wellhead and Tree Equipment ISO 13628-4 (API 17D)(2010) – Design and Operation of Subsea Production Systems – Part 4: Subsea Wellhead and Tree Equipment API Standard 53, 4thEdition (2012) – Blowout Prevention Equipment Systems for Drilling Wells API6X (2014) – Design Calculations for Pressure-Containing Equipment

Downloaded Copy

Emad Jodeh

Lead Mechanical & Wellheads Specialist to
Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate No: LR26436068TA
Issue Date: 30/06/2026
Expiry Date: 29/06/2031

Type Approval Certificate

Ratings	Rating Working Pressure	15,000 psi
	Rating External Pressure	1,000 psi
	Temperature Range	Plus 2˚C to plus 121˚C (35˚F to plus 250˚F)
	Fluid Service	Sour Service
	Material Class	FF
	Product Specification Level	PSL 3G
	Performance Requirement	PR 2 – Including Annex F

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version:

The Design Appraisal Document LR26436068TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.