Certificate No: LR2004402TA
Issue Date: 24/06/2020
Expiry Date: 23/06/2025

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Wärtsilä Japan, Ltd.**
Address	7 Chome-14-37, Mukaishinjomachi, Toyama, 930-0916, Japan
Place of Production	Wärtsilä Japan, Ltd. 7 Chome-14-37, Mukaishinjomachi, Toyama, 930-0916, Japan
Type	Stern Tube Seals
Description	Stern tube seal for the prevention of oil leakage and/or water ingress
Trade Name	Sternguard MKII/OLS2/OLS2-P/OLS2-P-N (Forward) Sternguard MKII/OLS3/ OLS3-P/OLS3-P-N (Aft)
Application	Oil bath type stern tube sealing arrangement for operation in ships fitted with suitable oil lubricating system. LR SCM/*IWS notation.
Specified Standard	Lloyd's Register's Rules and Regulations for the Ships, Part 5, Chapter 6 (January 2020)
Ratings	Nominal seal size range (mm): 155~1250 (MKII)/ 115~1250 (OLS2, OLS3, OLS2-P, OLS3-P, OLS2-P-N, OLS3-P-N) Minimum shaft diameter (mm): 136 (MKII)/ 80 (OLS2, OLS3, OLS2-P,OLS3-P, OLS2-P-N, OLS3-P-N)

Downloaded Copy

Yasushi Sawada

Machinery & Piping Group Leader to Lloyd's Register Group Ltd
A member of the Lloyd's Register Group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Maximum shaft diameter (mm):
1172 (MKII, OLS2, OLS3 OLS2-P, OLS3-P, OLS2-P-N, OLS3-P-N)

Other Conditions

1) Where the seals are intended to be installed in a ship classed or intended to be classed with Lloyds Register (LR), the stern tube seals are to be found to function to the attending LR Surveyor's satisfaction when fitted and tried under full working conditions.
2) The sealing system is to be installed in accordance with the manufacturer's instructions.
3) Where applicable, instructions for installation and maintenance specific to G123 composite seal casings are to be part of the manufacturer's instructions.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Group Ltd of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document No. LR2004402TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.