Certificate No: LR21398351ALP
Issue Date: 17/11/2020
Expiry Date: 16/11/2025

Approved Chocking Resin

Manufacturer	**ITW Polymers & Fluids**
Address	100 Hassal Street, Wetheril Park, New South Wales, 2164, Australia
Product	**CHOCKFAST ORANGE PR 610 TCF**
Type	Chocking Resins
Approval	Maximum loading of 5.0MPa for a maximum service temperature of 80°C provided the following conditions are met: a) Installation shall be carried out in accordance with Chockfast Orange installation procedure b) Exotherm temperature of the poured chocking resin to be measured ALL INDIVIDUAL MEASURED MINIMUM BARCOL HARDNESS SHALL BE 40 OR GREATER
Data	Surveyor site inspection, approval test data based on 50mm chock pour test samples

This certificate is issued to the company named above. Based on the examination of the data submitted the product described is considered acceptable for use in constructions built under Lloyd's Register's survey. This acceptance is subject to Lloyd's Register being informed of any changes in or modifications to the product and the product being used in accordance with the manufacturer's instructions and with the relevant requirements of Lloyd's Register's Rules and Regulations.

Downloaded Copy

Mayur Jogia

Lead Specialist - Non-Metallics to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.