Certificate No: LR26433756TA
Issue Date: 08/09/2026
Expiry Date: 07/09/2031

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Trelleborg Clermont-Ferrand SAS**
Address	ZI LA COMBAUDE, Clermont-Ferrand, 63050, France
Place of Production	Trelleborg Clermont-Ferrand SAS ZI LA COMBAUDE, Clermont-Ferrand, 63050, France
Type	Fuel Tanks And Fuel Hoses
Description	Boat fuel hoses style R1 (DN 5 to 25) consisting of inner tube of black, smooth, oil and fuel resistant NBR, reinforcement of high tensile textile cord PVA and cover of black, smooth with cloth impression, oil, flame, seawater, abrasion, weather and ozone resistant CR.
Trade Name	Boat Fuel Hoses
Application	Fire resistance fuel hoses for small craft up to 24 m hull length
Specified Standard	Directive 2013/53/UE on recreational craft and personal watercraft ISO 7840 : 2021 – A type 1, Small Craft - Fire Resistant Fuel Hoses, SAE J1527 : 2022 Marine Fuel Hoses USCG type A – class 1 and class 2 – style R1 and R2, LR Test Specification No. 1: - ENV1 controlled environments only, to producer's

Downloaded Copy

Torsten Schroeder

Engineering - Piping/ Decarbonisation - Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

specification

Ratings	Working pressure:	3,4 bar for DN 5 to 10 mm 2,5 bar for DN 12,5 to 25 mm
	Temperature range:	-30 to +100°C

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR22265260TA, previous 19/20059

The Design Appraisal Document TSO/26-065384, previous HTS/ENS 39598-19, Issue No. 1 and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.