Certificate No: LR22510987TA
Issue Date: 21/12/2022
Expiry Date: 02/09/2027

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Conductores Monterrey, SA de CV.**
Address	Ave. Conductores No. 505, Col. Constituyentes de Queretaro, San Nicolas De Los Garza, NL, Mexico
Place of Production	Conductores Monterrey, SA de CV. Ave. Conductores No. 505, Col. Constituyentes de Queretaro, San Nicolas De Los Garza, NL, Mexico
Type	Control Cables
Description	Flame retardant, single and multicore, multipairs and multitriads, shielded/ unshielded, armoured/unarmoured, over-sheathed (jacket) control and instrumentation cables.
Trade Name	P & T/N
Application	Marine, offshore and industrial applications
Specified Standard	IEEE-1580: 2021, IEEE–45: 2002, UL 1309: 2022, CSA C22.2 No 245-17
Ratings	Type P Size AWG 10 to 22, number of Cores 2 to 91, 600/1000V, max conductor temperature 100C Type T/N

Downloaded Copy

Matthew Partyka

Technical Lead – Marine Electrotechnical to
Lloyd's Register Canada Limited
A member of the Lloyd's Register group

237 Brownlow Avenue, Suite 200, Dartmouth, NS.
B3B2C7, Canada

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate No: LR22510987TA
Issue Date: 21/12/2022
Expiry Date: 02/09/2027

Type Approval Certificate

Size AWG 10 to 20, Number of cores 2 to 91, 300 or 600/1000V , max conductor temperature 90C

Other Conditions Installation of this equipment for marine applications is to be in accordance with current Lloyd's Register Rules and Regulations.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Canada Limited of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: 09/60009(E6)

The Design Appraisal Document LR22510987TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

237 Brownlow Avenue, Suite 200, Dartmouth, NS.
B3B2C7, Canada

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.