Certificate No: LR2002671TA
Issue Date: 14/01/2020
Expiry Date: 06/09/2023

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**HONG TAI ELECTRIC INDUSTRIAL CO., LTD.**
Address	No. 2, Kuo Chien 1st Road, Kuan-Yin dist., Taoyuan City, Taiwan
Place of Production	HONG TAI ELECTRIC INDUSTRIAL CO., LTD. No. 2, Kuo Chien 1st Road, Kuan-Yin dist., Taoyuan City, Taiwan
Type	Power Cables
Description	Power cable, 3 core 600V: XLPE-LSNH
Trade Name	Hong Tai
Application	Marine, offshore and special public area such as airports, subways, and rapid transit systems.
Specified Standard	IEC 60332-1, IEC 60332-3
Ratings	Conductor: Coper annealed to CNS 1364 Conductor shield: Semi conductor to CNS2655 table 2 Insulation: XLPE to CNS 2655 section 3.3 Filler: LSNH Sheath: LSNH to BS6724 and BS6469 Construction: CNS 2655 table 3 Oxygen index: ASTM-D2863

Downloaded Copy

Ke Lin Zhang

Senior Specialist to Lloyd's Register
Classification Society (China) Co Ltd
A member of the Lloyd's Register group

19th Floor, 550 Yan An dong Road, Shanghai,
Huangpu District, China

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate No: LR2002671TA
Issue Date: 14/01/2020
Expiry Date: 06/09/2023

Type Approval Certificate

Temperature index: NES 715
Rated voltage: 600V, conductor size: 22mm^2, No. of cores: 3
Maximum conductor temperature: 90°C

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Classification Society (China) Co Ltd of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document No. LR2002671TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

19th Floor, 550 Yan An dong Road, Shanghai,
Huangpu District, China

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.