Certificate No: LR2621671TA
Issue Date: 22/07/2025
Expiry Date: 21/07/2030

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**ScandFlow AB**
Address	Agneshögsgatan 22, Motala, 591 71, Sweden
Place of Production	ScandFlow AB Agneshögsgatan 22, Motala, 591 71, Sweden
Type	Flexible Hoses
Description	Flexible corrugated, steel hose assemblies with a single external wire braiding with permanent end fittings, optional as flanged, double walled version
Trade Name	Tubiflex SP.T.9750
Application	Marine, offshore and industrial piping systems, as short joining lengths to accommodate relative movement between items of machinery connected to permanent piping systems. Double walled hose assemblies are approved for gas fuel systems, not subjected to vibration or pressure pulsation with fluid media.
Specified Standard	Lloyd's Register's Rules and Regulations for the Classification of Ships (Part 5, Chapter 12, Section 7)
Ratings	Material; Hose: 316 stainless steel, Braid: 304 stainless steel & End fittings: 316L stainless steel

Downloaded Copy

Torsten Schroeder

Engineering - Piping/ Decarbonisation -
Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Hose diameter (mm): 10 to 150
Max. operating pressure (bar): 75 to 10
See manufacturer's product catalogue for further detail ratings.

Hose diameter (DN):	Max. operating pressure (bar) at 20^0 C:
10	75
12	70
15	65
20	50
25	40
32	35
40	30
50	25
65	20
75	18
100	14
125	10
150	10

Other Conditions

1. Hoses are to be selected, installed and tested in accordance with the manufacturer's recommendations and Lloyd's Register's Rules and Regulations for the Classification of Ships, Part 5, Chapter 12, Section 7.
2. Materials for hoses and fittings are to be manufactured and tested in accordance with the requirements for Class I piping systems.
3. For use on ships, hose screwed end connectors are limited to sizes up to 2" (DN50).
4. Hoses are not approved for use in piping systems where pressure pulses and/or high levels of vibration are expected to occur in service.
5. Each flexible hose with end fittings is to be provided with the manufacturer's pressure test report and conformity of the production and the following details are to be permanently marked:
• Manufacturer's name or trademark.
• Date of manufacture (month/year).
• Designation type reference.
• Nominal diameter.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

- Pressure rating.
- Temperature range.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR2101695TA, (previous 10/0048(E1))

The Design Appraisal Document TSO/25-044274 and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.