Certificate No: LR24150793TA
Issue Date: 01/08/2023
Expiry Date: 31/07/2028

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**VOSS Fluid GmbH**
Address	Luedenscheider Str.52-54, Wipperfuerth, 51688, Germany
Type	Compression Fittings
Description	Steel or stainless steel adjustable pipe coupling with 24° tapered connection and FKM-O-Ring.
Trade Name	VOSS 24° Taper Couplings
Application	General use in marine, offshore and industrial piping systems. Restrictions (not to be used): 1. starting/control air and CO2 systems. 2. inside machinery spaces of category A or accommodation spaces for inert gas main lines 3. fire extinguishing systems which are not always filled with water
Specified Standard	LR Rules and Regulations for the Classification of Ships, July 2024

Downloaded Copy

Torsten Schroeder

Engineering - Piping/ Decarbonisation -
Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate No: LR24150793TA
Issue Date: 01/08/2023
Expiry Date: 31/07/2028

Type Approval Certificate

Ratings

Series	Pipe outside diameter (mm)	Nominal pressure (bar)
L (light)	6 to 10	500
	12 to 18	400
	22 to 42	250
S (heavy)	6 to 10	800
	12 to 16	630
	20 to 38	420

Additional Tests Repeated assembly, leakage, burst pressure, hydraulic impulse and vibration, flame resistance tests conducted.

Other Conditions Trade mark “VOSS” to be shown on each coupling. The pipe couplings to be selected and installed as per producer’s recommendations and instructions.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: 93/20050(E5)

The Design Appraisal Document TSO/24-017822, prev. HMD 13340-04, Rev. 3 and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.