Certificate No: LR2002185TA
Issue Date: 06/03/2020
Expiry Date: 05/03/2025

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**WAM 926 New Zealand Ltd.**
Address	48-50 Patiki Road, Avondale, New Lynn, Auckland, 15312, New Zealand
Place of Production	Wellcall Hose (M) Sdn Bhd Plot 48, Jalan Johan 2/5, Kawasan Perindustrian Pangkalan II, Fasa II, Lahat, Pusing, Perak, 31550, Malaysia
Type	Flexible Hoses
Description	WAM Compressed air hose ISO2398/1C/L-T (Extrusion type) WAM Compressed air hose ISO2398/2C/N-T (Mandrel built) WAM Compressed air hose ISO2398/2B/N-T (Extrusion type)
Trade Name	WAM Compressed Air Hose
Application	Flexible hose for conveying compressed air.
Specified Standard	ISO 2398: 2006
Ratings	ISO 2398/1C/L-T(Extrusion type): Hose diameters (inch): ¼'" to 2" Pressure rating (MPa): 1.0 Temperature rating (℃): -40 ~ +65 ISO 2398/2C/N-T (Mandrel built):

Downloaded Copy

Sobhith Hariharan

Senior Specialist - Marine to Lloyd's Register Singapore Pte Ltd
A member of the Lloyd's Register group

1 Fusionopolis Place, #09-11 Galaxis, 138522, Singapore

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate No: LR2002185TA
Issue Date: 06/03/2020
Expiry Date: 05/03/2025

Type Approval Certificate

Hose diameters (inch): ¾‴ to 4″
Pressure rating (MPa): 1.6
Temperature rating (℃): -25 ~ +70

ISO 2398/2B/N-T(Extrusion type):
Hose diameters (inch): ¼‴ to 2″
Pressure rating (MPa): 1.6
Temperature rating (OC): -25 ~ +70

Other Conditions This hose is supplied without end fittings. End fittings are to be fitted and tested in accordance with ISO 2398 to ensure that the assembly is compliant with ISO 2398.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Singapore Pte Ltd of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document No. LR2002185TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

1 Fusionopolis Place, #09-11 Galaxis, 138522,
Singapore

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.