Certificate No: LR2487014TA
Issue Date: 20/09/2024
Expiry Date: 27/01/2028

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Prysmian Group Netherlands BV**
Address	Abel Tasmanstraat 1, Emmen, 7821 AN, Netherlands
Type	Cables Accessories
Description	Flame retardant, halogen free crosslinked polyethylene (XLPE) insulated, SFH1 over sheathed, braided, instrumentation and communication cable.
Trade Name	TXOI 250V
Application	Fixed wiring on ships offshore and industrial installations.
Specified Standard	IEC 60092-376 ed 3.0, IEC 60092-351 ed 3.0, IEC 60092-359 SHF1 ed 1.2, IEC 60332-1 ed 1.1, IEC 60332-3-22, Cat. A, ed 2.0, IEC 60754-1 ed 3.1 & -2, ed 2.1, IEC 61034-1&2, ed 3.2.
Ratings	Rated voltage 250V Range:

Conductor cross section	Number of pairs
0,75 mm^2	1, 2, 4, 7, 10, 14, 19 or 24
0,5 mm^2	1, 2, 4, 7, 10, 14, 19 or 24

Downloaded Copy

Thorsten Wolff

Electrical & Control - Senior Specialist to
Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

	1,5 mm^2	1, 2, 4, 19 or 30

Other Conditions

Maximum continuous conductor temperature 90°C.
The Type Approval does not eliminate the need for normal inspection and survey procedures required by the Rules and Regulations.
If the specified standards are amended during the validity of this certificate, the product is to be re- approved prior to it being supplied to vessels to which the amended standards apply.

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: 18/30032

The Design Appraisal Document TSO-24-016844-SR-TW and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.