Certificate No: LR2658740TA
Issue Date: 23/12/2025
Expiry Date: 22/12/2030

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Goetze KG Armaturen**
Address	Schlieffenstraße 41, Ludwigsburg, 71636, Germany
Type	Regulating Valves
Description	Pressure reducer with pressure-relieved single seat valve, mostly with built-in dirt trap Connections: socket joints, threads or flanges For media: water, neutral and non-sticking liquids, compressed air and neutral gas; Design features: straight-way types; adjustable under operation conditions without media escaping to outside; Body materials: red brass, brass or stainless steel; Gaskets: NBR, EPDM, FKM, PTFE
Trade Name	681, 682, 683, 481, 482, 484, 684, 9000, 9040, 9060, 382, 9160, 2980, 9140, 9061
Application	valves for liquids and gaseous media in marine and offshore installation
Specified Standard	Lloyd´s Register Rules and Regulations for the Classification of Ships, July 2025
Ratings	Size range : DN8 to DN125 primary pressure: up to 60 bar depending on type

Downloaded Copy

Torsten Schroeder

Engineering - Piping/ Decarbonisation -
Senior Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

secondary pressure: 0,5 to 50 bar depending on type
Temperature range: -50°C up to +200°C depending on type

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR2089502TA, previous 10/20054(E1)

The Design Appraisal Document TSO/25-044468, previous ENS 36135-10, Issue No. 2 and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.