Certificate No: LR22262419TA
Issue Date: 22/06/2022
Expiry Date: 23/11/2026

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	**Chiang Jiang Marketing SDN. BHD**
Address	LOT 20Jalan E ¼Kawasan Perindustrian, Taman Ehsan, Kuala Lumpur, 52100, Malaysia
Place of Production	Wellcall Hose (M) Sdn Bhd Plot 48, Jalan Johan 2/5, Kawasan Perindustrian Pangkalan II, Fasa II, Lahat, Pusing, Perak, 31550, Malaysia
Type	Flexible Hoses
Description	Rubber hose for sand and grit blasting applications Inner Tube: Smooth bore blended SBR rubber Reinforcement: High strength polyester braided cords Cover: High abrasion and ozone resistant blended elastomeric rubber Electrically conductive, using a conductive rubber layer marked “Ω” grade
Trade Name	UNIGAWA
Application	For use with sand and grit blasting applications
Specified Standard	ISO 3861 : 2021

Downloaded Copy

12th Floor, Chong Hing Finance Centre, No. 288
Nanjing West Road, Shanghai, Huangpu District,
200003, China

Qing Dong

Specialist to Lloyd's Register Classification Society (China) Co Ltd
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate No: LR22262419TA
Issue Date: 22/06/2022
Expiry Date: 23/11/2026

Type Approval Certificate

Ratings	Hose Inside Diameter (mm):	12.5 ~ 51
	Maximum Working Pressure (bar):	6.3
	Temperature Range (˚C):	-25~70
Other Conditions	This hose is supplied without end fittings. End fittings are to be fitted and tested in accordance with ISO 3861 : 2021 to ensure that the assembly is compliance with ISO 3861 : 2021.	

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register Classification Society (China) Co Ltd of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: 16/80091

The Design Appraisal Document LR22262419TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Downloaded Copy

12th Floor, Chong Hing Finance Centre, No. 288
Nanjing West Road, Shanghai, Huangpu District,
200003, China

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.